

File E136791
Project 07NK01111

November 9, 2007

REPORT

ON

POWER SUPPLIES, INFORMATION TECHNOLOGY
EQUIPMENT INCLUDING ELECTRICAL BUSINESS EQUIPMENT

SL Power Electronics Corp.
Ventura, CA

Copyright © 2007 Underwriters Laboratories, Inc.

Underwriters Laboratories Inc. authorizes the above
named company to reproduce this Report provided it is
reproduced in its entirety.

DESCRIPTION

PRODUCT COVERED:

USL, CNL - PoE Injector, Model PW182, followed by additional suffixes as noted under the Part Number Designation.

GENERAL CHARACTER AND USE:

This product is a Power over Ethernet (PoE) Injector incorporating semiconductor components in the primary circuit and an isolating transformer. The input is supplied from an appliance inlet, and the unit is provided with RJ-45 connectors for connection to an ethernet network that does not connect to outside plant and to transfer data and power to another device. The outputs are considered LPS, SELV, and non-energy hazardous.

ELECTRICAL RATINGS:

| Model | Input, 50-60 Hz. | | Output, d.c. | |
|---|------------------|-----|--------------|------|
| | V | A | V | A |
| PW182-XA-48-XX-X-XX, PW182-XC-48-XX-X-XX | 100-240 | 0.6 | 48 | 0.4 |
| PW182-XB-48-XX-X-XX, PW182-XD-48-XX-X-XX | 100-240 | 0.6 | 48 | 0.35 |

NOTE: The marked output voltage may be less than the rated output voltage per the table, provided that the output current remains the same or less as shown in the table.

PART NUMBER DESIGNATION:

| | | | | | | |
|--------------|----------|----------|-----------|-----------|----------|-----------|
| <u>PW182</u> | <u>X</u> | <u>X</u> | <u>XX</u> | <u>XX</u> | <u>X</u> | <u>XX</u> |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |

1. Model Number for family related designs.
2. Manufacturing Location: A-Z.
3. Design Revision Changes: A, C = 0.35 A.
B, D = 0.4 A.
4. Tabulated output voltage as noted in Electrical Ratings, above.
5. Number Options: 00-99.
6. Input Options: F = Class I, C14 Appliance inlet.
N = Class II, C8 Appliance inlet.
Q = Class II, C18 Appliance inlet.
7. Number Options: 00-99.

ENGINEERING CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

Special Considerations - The following items are considerations that were used when evaluating this product.

USL/CNL indicates investigation to the U.S. and Canadian (Bi-National) Standard for Safety of Information Technology Equipment - Part 1: General Requirements, CAN/CSA-C22.2 No. 60950-1-03, UL 60950-1, First Edition, dated April 1, 2003, with Revisions through and including July 7, 2006.

The equipment has been evaluated for use in a Manufacturer's Recommended ambient (Tma) of 25°C.

The equipment is considered movable, Class I (earthed) or Class II (double insulated), pluggable Type A, uses a detachable power cord, intended for use on a TN power system.

This product has been investigated for pollution degree 2 applications. It is considered for IPX0 ordinary protection against the ingress of water.

Disconnect Device - The following component is considered the equipment disconnect device: Appliance Inlet.

Limited Power Source: All outputs are LPS.

The RJ-45 connectors were not evaluated for connection to outside plant and should only be connected to ethernet networks and devices that do not directly exit the building.

MODEL DIFFERENCES

Models are identical to each other except for differences in secondary circuitry, pin out on ethernet connectors, output ratings (as noted above) and aesthetics.