

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE CERTIFICATS D'ESSAIS DES EQUIPEMENTS ELECTRIQUES (IECEE) METHODE OC

CB TEST CERTIFICATE

CERTIFICAT D'ESSAI OC

Product
Produit

Built-in Power Supply

Name and address of the applicant
Nom et adresse du demandeur

SL POWER ELECTRONICS CORP
BLDG A, 6050 KING DR
VENTURA CA 93003, USA

Name and address of the manufacturer
Nom et adresse du fabricant

SL POWER ELECTRONICS CORP
BLDG A, 6050 KING ST
VENTURA CA 93003, USA

Name and address of the factory
Nom et adresse de l'usine


INDUSTRIAS S L S A DE C V
CIRCUITO SIGLO XXI 2055 COL PARQUE INDUSTRIAL EX-XXI 21254 MEXICALI BC
MEXICO

Note: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la 2^{ème} page

Additional Information on page 2
See Page 2

Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

Trademark (if any)
Marque de fabrique (si elle existe)



Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeur

Model / Type Ref.
Ref. De type

GNT424CBE-115G, GNT4WXYZ-XXXG, MINT1400VWXYZ,
SP1852G
See Page 2

Additional information (if necessary may also be reported on page 2)
Les informations complémentaires (si nécessaire, peuvent être indiqués sur la 2^{ème} page

Additionally evaluated to EN 60950-1:2006 / A11:2009 / A1:2010 / A12:2011; National Differences specified in the CB Test Report.

Additional Information on page 2

A sample of the product was tested and found to be in conformity with
Un échantillon de ce produit a été essayé et a été considéré conforme à la

IEC 60950-1(ed.2), IEC 60950-1(ed.2);am1

As shown in the Test Report Ref. No. which forms part of this Certificate
Comme indiqué dans le Rapport d'essais numéro de référence qui constitue partie de ce Certificat

E135803-A34-CB-4 issued on 2013-01-25, E135803-A34-CB-4 issued on 2013-01-25

This CB Test Certificate is issued by the National Certification Body

Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2013-01-27
Original Issue Date: 2013-01-24

Signature:

Jolanta M. Wroblewska

Model Details:

GNT4WXYZ-XXXG where W represents the output voltage which may be any number from 12 thru 48; X indicates the type of input connector which may be the letters A, B or C; Y indicates the type of output connector which may be the letter B or T; Z indicates the type of cover or cover/fan options which may be blank or the letter E or T; -XXX indicates value added configurations that have no impact on safety which may be any number from 001 thru 999; suffix "-103" indicates improved EMI circuit; suffix "-112" indicates use of low-speed fan mounted on top of cover.

MINT1400VWXYZ where V indicates the design version which may be the letter A to indicate standard mini cover or C to indicate optional cover/fan; W represents the output voltage which may be any number from 12 thru 48; X indicates the type of output connector which may be any number from 01 thru 99; Y indicates the type of input connector which may be the letter L; Z indicates the configuration options which may be the number 01 for standard configuration or 02 thru 99 for modifications that have no impact on safety.

Factories:

SL XIANGHE POWER ELECTRONICS CORP
NO 4 SHUANGXING NORTH RD XIANGHE ECONOMIC & TECHNOLOGICAL DEVELOPMENT ZONE XIANGHE
HEBEI 065402
CHINA

Ratings:

Model GNT4WXYZ-XXXG:

Input: 100-240 V ac, 5.5-2.5 A, 50/60 Hz

Output: 12 thru 48 V dc, 400 W maximum with forced air cooling.

Model SP1852G:

Input: 100-240 V ac, 5.0-2.0 A, 50/60 Hz

Output: +24 V dc/12.5 A maximum with forced air cooling

Model GNT424CBE-115G:

Input: 100-240 V ac, 5.5-2.5 A, 50/60 Hz

Output: +24 V dc/15.6 A maximum with forced air cooling.

Model MINT1400VWXYZ:

Input: 100-240 V ac, 5.5-2.5 A, 50/60 Hz

Output: 12 thru 48 V dc, 400 W maximum with internal forced air cooling or minimum 27 CFM external forced air cooling or 195 W maximum with convection cooling or 250 W maximum with convection cooling and unit mounted to aluminum plate.

Additional Information:

The original report was modified to include the following changes/additions:
Modify factories information, see test report.

Additional information (if necessary)**Information complémentaire (si nécessaire)**

- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2013-01-27

Original Issue Date: 2013-01-24

Signature:

Jolanta M. Wroblewska