

# External Power Supply International Efficiency Level V



**ErP Phase 2** 

By Maggie Nadjmi March 16<sup>th</sup> 2011

## **Background**

- More than **one billion** external power supplies are sold worldwide each year
- Majority of these supplies are used to convert the high voltage **AC** to the low voltage **DC** for powering small electronic office equipment or medical products.
- This conversion will produce **wasted heat** which brings the overall **efficiency** to less than 85%
- Considering 100MWatt of electricity consumed, efficiency improvement of only 1% will result in energy saving of 1MWatt. This number becomes significant in reducing wasted power for over one billion external power supplies used globally
- Through extensive **international** collaboration, a standard test method and performance metric of **no load** and **average efficiency** have been established
- The **average efficiency** is calculated based on **25**% increments in output load from 25% to 100%
- The first mandatory requirement by **EPA** in US was meeting efficiency **Level IV** legislated under **EISA**
- **EPA** and international environmental regulatory bodies have adopted **Level V** efficiency standards effective **2011**
- CE marking denotes the compliance to efficiency requirements set by European Commission under EU(EC) No 270/2009 Phase II directive

### **Product Transition**

#### EISA2007, CEC Efficiency Level V EU (EC) No 278/2009 Phase II

Output Voltage ≥12VDC

Output Power	Minimum Average Efficiency	Maximum No load Consumption	Effective Date	SL Power New ITE Product Family Level V	SL Power Existing ITE Family Level IV Do not meet Level V
0 to 51 Watts	Varies from 81% to 87%	≤0.3Watts	4/27/2011 in Europe	CENB1010 (10Watts) CENB1020 (20Watts)	PW170 (10Watts) PW172 (20Watts)
	Depends on Wattage Level			CENB1030 (30Watts) CENB1040 (40Watts)	PW173 (30Watts) PW153 (40Watts)
>51 to 250 Watts	≥87%	≤0.5Watts	4/27/2011 in Europe	CENB1050 (51.1Watts) CENB1060 (60Watts) CENB1080 (80Watts) CENB1090 (90Watts) CENB1100 (100Watts) MENT1150 (150Watts) MENT1220 (220Watts)	PW174 (60Watts) PW156 (75Watts) CENT1120 (120Watts)

### **Medical Products**

#### EISA2007, CEC Efficiency Level V EU (EC) No 278/2009 Phase II

#### **Output Voltage ≥12VDC**

Output	SL Power	SL Power Existing Medical Family
Power	New Medical Family	Level IV
	Level V	Do not meet Level V
0 to 51 Watts	MENB1010 (10Watts)	MW170 (10Watts)
	MENB1020 (20Watts)	MW172 (20Watts)
	MENB1030 (30Watts)	MPW173 (30Watts)
	MENB1040 (40Watts)	MW153 (40Watts)
>50 Watts	MENB1050 (51.1Watts)	MW174 (60Watts)
	MENB1060 (60Watts)	MW155 (75Watts)
	MENB1080 (80Watts)	MW156 (110Watts)
	MENB1090 (90Watts)	
	MENB1100 (100Watts)	
	MENT1150 (150Watts)	
	MENT1220 (220Watts)	
	, ,	

## Take away Points

- Look for the **V** and the CE marking on the power supply label
- ErP2 requirements goes in effect by 27th of April 2011
- Level V products should be specified for new designs
- There is no specific requirement for Medical External supplies to meet any specific efficiency level. However, customers are starting to request level V for new designs
- There are some countries requiring MEPS (minimum energy performance requirements) certifications. Australia, New Zealand, Canada, and South Korea are among them
- After April 27<sup>th</sup>, CE marking will include declaration of conformity to EU (EC) No 270/2009 Phase II requirements

## Thank you!